



OROMECCANICA COMMERCIALE SRL

v. G. Ferraris 260-264 52100 Arezzo Italy
Tel. +39.0575.383151 Fax +39.0575.383152
E-mail oromeccanica@oromeccanica.com

TRAFILA AD 11 PASSAGGI PER FILI CAPILLARI FINO A 0.028 mm WIREDRAWING MACHINE 11 PASSAGES FOR CAPILLARY WIRES 0.028 mm



Machine realized for wiredrawing capillary wires of \varnothing 0.028 mm.

The cones are motorized and made in a special hard wearing material and cooled together with the drawing dies. The traction and holder wire reel is motorized with converter to permit the continuous adjusting of the traction force by the use of a pendulum device.

HEIGHT 1340 LENGTH 1970 WIDTH 1090
PASSAGES OF WIREDRAWING OPERATIONS
N. 11

DRAWING SPEED 0 - 540 mt/1'
MAXIMUM IN GOING DIAMETER 0.80 mm.
MINIMUM COMING OUT DIAMETER 0,028 mm.
SIZES OF THE IN GOING AND COMING OUT
HANKS EXTERNAL DIN 125.
MAIN MOTOR POWER HP 15.
MOTOR POWER COLLECTING AND REELING
CONE HP 0,5
MOTOR POWER PUMP HP 0,5.
FEEDING 380 V.
WEIGHT 850 Kg.
WEIGHT WITH PACKING 1030 Kg.

Macchina realizzata per trafilare fili capillari \varnothing 0.028 mm.

I coni sono entrambi motorizzati e realizzati con materiale speciale antiusura e raffreddati insieme ai fori di trafilatura. L' aspo di trazione e raccolta filo è motorizzato con convertitore per consentire la regolazione continua della trazione tramite dispositivo a pendolo.

ALTEZZA 1340 mm. LUNGHEZZA 1970 mm.
LARGHEZZA 1090 mm.
PASSAGGI DI TRAFILATURA N. 11
VELOCITÀ DI TRAFILATURA DA 0 A 540 mt/1'
Ø MASSIMO FILO IN ENTRATA 0.80 mm
Ø MINIMO FILO IN USCITA 0.028 mm
DIMENSIONI ROCCHETTI IN ENTRATA E USCITA DIN
125
POTENZA MOTORE PRINCIPALE HP 15.
POTENZA MOTORE ASPO DI RACCOLTA
E BOBINATORE HP 0,5
POTENZA MOTORE POMPA HP 0,5
ALIMENTAZIONE 380 V.
PESO 850 Kg.
PESO CON IMBALLO 1030 Kg.